

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 October 2004 (14.10.2004)


PCT

(10) International Publication Number  
**WO 2004/088044 A1**

- (51) International Patent Classification<sup>7</sup>: **E01F 15/14**
- (21) International Application Number:  
PCT/NL2004/000217
- (22) International Filing Date: 31 March 2004 (31.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
1023057 31 March 2003 (31.03.2003) NL
- (71) Applicant (for all designated States except US): **VAN DEN DONKER, Cornelis** [NL/NL]; Dc Kolk 51-53, NL-8255 PD Swifterbant (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **ENGELBRECHT, Don, Stephan** [NL/NL]; Kijkduin-straat 16, NL-1055 XZ Amsterdam (NL).
- (74) Agents: **VAN WESTENBRUGGE, Andries** et al.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: **PILLAR PROTECTION ASSEMBLY**



(57) Abstract: Pillar protection assembly (1) consisting of a plastic sleeve (7) inside which a number of plastic foam blanket sections (6) are arranged. The sleeve (7) can be provided with information on the outside and has a closure (8) so as to fix this to the pillar (5) after it has been wrapped around the latter. The plastic foam material of the plastic foam blanket (6) consists of a foam matrix in which particles are incorporated that preferably consist of a recycled material. The plastic foam material used can be polyether or polyurethane.

WO 2004/088044 A1



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## Pillar protection assembly

The present invention relates to a pillar protection assembly comprising a plastic foam blanket, which can be fitted around a pillar, as well as a plastic sleeve fitted around  
5 said blanket, wherein said plastic foam has a foam matrix in which particles differing from the matrix with a particle size of between 0.1 and 10 mm are incorporated.

A pillar protection assembly of this type is disclosed in DE 20116169 U1. In this publication a jacket made of recycled material in which granulate particles are incorporated is described.

10 In GB 2 209 041 A1 a protection to be fitted around a round pillar is described, consisting of an inner layer of foam material and an outer layer to which information can be applied.

The application for the protection described in this publication appears to be in schools, clubs and the like.

15 The aim of the present invention is to provide a pillar protection assembly that can be used to protect cars and is easy to fit. More particularly, the aim is to provide a pillar protection assembly that can be used in car parks or in other locations where cars have to be manoeuvred accurately and where it is a regular occurrence that cars scrape against concrete pillars and the like, as a result of which such vehicles can be damaged.

20 It has been found that conventional foam materials are not suitable for, on the one hand, offering adequate protection to the cars and, on the other hand, being able to be fitted in a reasonable size around the pillar in an optically correct manner.

The aim of the present invention is to provide a pillar protection assembly that does not have these disadvantages and is easy to fit on pillars of any shape.

25 This aim is realised with a pillar protection assembly as described above in that said foam blanket comprises a number of sections a distance (a) apart joined by a strip material.

By providing a gap it is possible in a simple manner to fit the plastic foam blanket around pillars, no creases and/or compressed portions being produced as a result of the difference in the length of the periphery between the inside of the foam blanket wound  
30 around the pillar and the outside thereof. This applies both for fitting of both round pillars and pillars of other shapes.

The mutual spacing between the sections of the foam blanket can be achieved by locally fitted strips. However, it is also possible to start from a continuous web of material,

foam blanket sections being applied regular distances apart.

The present invention is in particular applicable to polygonal and more particularly square or rectangular pillars. In order to achieve correct positioning of the pillar protection assembly around the pillar it is proposed according to the present invention to build up the blanket from a number of blanket sections that are arranged spaced apart on the sleeve (unfolded). The distance between the sections corresponds to the thickness of the foam material. In this way accurate taut fitting around a pillar can be achieved. Preferably, the sleeve is supplied in the unfolded state and there are closure means to close the sleeve after wrapping it around a pillar. Such closure means can comprise a zip but can also comprise other known closure means. There is optionally a lock or the like to ensure that unauthorised persons are not able to remove the pillar protection assembly without substantial damage.

Polyether and polyurethane are mentioned as examples of the plastic foam used for the matrix. A relatively high density of the material is important for the present invention. An appreciable impact strength is also important. According to the present invention this is preferably between 5 - 250 kPa according to DIN 53571.

The material must preferably also have a residual compressive deformation after 90 % deformation of 1 - 20 % according to DIN 53572.

It has been found that if materials with such properties are used the motorist can immediately recognise if he touches the pillar protection assembly but, on the other hand, damage to the vehicle is prevented.

According to an advantageous embodiment of the invention, an auxiliary sleeve is fitted around the sleeve. Such an auxiliary sleeve can easily be removed and can bear information that can be changed. As a result it is possible, starting from a basic pillar protection assembly, to fit notices around it that change as desired.

The subject invention will be explained in more detail below with reference to an illustrative embodiment shown in the drawing. In the drawing:

Fig. 1 shows the use of a pillar protection assembly according to the invention;

Fig. 2 shows a cross-section through a pillar provided with the protection assembly according to the invention;

Fig. 3 shows part of the pillar protection assembly according to the invention in the unfolded state; and

Fig. 4 shows a cross-section of the foam material used.

In Fig. 1 a pillar protection assembly is indicated by 1. This is provided with information 2. This can be used in car parks or in other locations where contact of moving objects with a stationary concrete pillar is not desired.

It can be seen from Fig. 2 that such a pillar of a multi-storey car park is indicated by 5. This is essentially of rectangular construction. The pillar protection assembly 1 according to the invention has been fitted around it. This consists, as can be seen in conjunction with Fig. 3, of a number of sheets of foam material 6 that have been applied with a spacing 11 to a piece of sailcloth material 7. Only one end of the sailcloth material 7 is indicated and this is provided with a zip 8. The corresponding part of the zip 8 is on the other end of the sailcloth material. The spacing 11 corresponds to the thickness of the sheets of foam material so that a taut rectangular construction can be obtained when the pillar protection assembly according to Fig. 3 is wrapped around a pillar. This can be seen, inter alia, from Figs 1 and 2.

The zip 8 can be provided with a fitting for a lock or the like to prevent removal by unauthorised persons.

It is also possible to fit an easily replaceable separate further sailcloth section 9 (auxiliary sleeve), which can likewise be closed by means of a closure such as zip 10, around the sailcloth section 7. As a result it is possible temporarily to provide other (advertising) information around the pillar assembly.

As indicated above, the material that faces outwards preferably consists of sailcloth material that is not very susceptible to soiling and is easy to clean. The material can optionally be treated, such as with Aquaseal, as a result of which a closed structure is obtained that does not pick up dirt easily.

According to the present invention the foam material preferably consists of recycled material that offers relatively high resistance to compression. Such a foam material is shown diagrammatically in Fig. 4 and consists of a matrix 20 in which particles 21 - 25 are incorporated. According to the present invention the matrix preferably consists of a foam material and more particularly of polyether or polyurethane material with relatively high relative density. At least the particles can consist of a recycled material and are preferably also foam particles. The particle size thereof is between 0.1 - 10 mm and more particularly between 1 and 7 mm.

The sailcloth material preferably consists of a fibre textile, such as of 100 % polyester fibres, which has been plasticised on one or both sides with a layer of polyvinyl

chloride. The relative density of such a cloth is preferably approximately 400 - 700 g/m<sup>3</sup>.

Both the cloth and the foam material are preferably made fire-retardant.

Variants that fall within the scope of the present invention and more particularly of the appended claims will be immediately apparent to those skilled in the art after reading

5 the above description.

## Claims

1. Pillar protection assembly comprising a plastic foam blanket, which can be fitted around a pillar, as well as a plastic sleeve fitted around said blanket, wherein said plastic  
5 foam has a foam matrix in which particles differing from the matrix with a particle size of between 0.1 and 10 mm are incorporated, characterised in that said foam blanket comprises a number of sections a distance (a) apart joined by a strip material.
2. Pillar protection assembly according to Claim 1, wherein said particles are bonded to the matrix by a binder.
- 10 3. Pillar protection assembly according to one of the preceding claims, wherein said particles comprise a recycled material.
4. Pillar protection assembly according to one of the preceding claims, for the protection of a polygonal pillar, wherein the number of sections of said blanket corresponds to a number of surfaces of said pillar to be protected.
- 15 5. Pillar protection assembly according to one of the preceding claims, wherein said distance is the thickness of the foam material.
6. Pillar protection assembly according to one of the preceding claims, wherein said sleeve is provided with information on the outside.
7. Pillar protection assembly according to one of the preceding claims, wherein said  
20 sleeve is split in the longitudinal direction and is provided with a closure.
8. Pillar protection assembly according to Claim 7, wherein said closure is a zip closure.
9. Pillar protection assembly according to one of the preceding claims, wherein said sleeve comprises a sailcloth material.
- 25 10. Pillar protection assembly according to one of the preceding claims, having an auxiliary sleeve provided with information to be fitted around said sleeve.


*Fig 1*

Fig 2






Fig 3



*Fig 4*



# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/NL2004/000217

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E01F15/14

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 E01F A63B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 596 106 A (KUNCZYNSKI JAN K) 24 June 1986 (1986-06-24) column 2, line 28 - line 66 figure 2	1-3,6-10
Y	DE 201 16 169 U (P V P POLYMER VERARBEITUNG UND) 13 February 2003 (2003-02-13) cited in the application page 3, paragraph 9 - page 4, paragraph 1; claims 1,3; figures	1-3,6-10
A	GB 2 209 041 A (MITCHELL GLYNDWR;MITCHELL SIMON NICHOLAS GLYNDW) 26 April 1989 (1989-04-26) cited in the application the whole document	1-10

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

14 September 2004

Date of mailing of the international search report

21/09/2004

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Geivaerts, D

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International Application No

PCT/NL2004/000217

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4596106	A	24-06-1986	NONE	
DE 20116169	U	13-02-2003	DE 20116169 U1	13-02-2003
GB 2209041	A	26-04-1989	NONE	